




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 1/267	A1	(11) International Publication Number: WO 99/35960 (43) International Publication Date: 22 July 1999 (22.07.99)
(21) International Application Number: PCT/US99/00740 (22) International Filing Date: 13 January 1999 (13.01.99) (30) Priority Data: 09/007,939 16 January 1998 (16.01.98) US (71) Applicant: UNIVERSITY OF FLORIDA [US/US]; 223 Grinter Hall, Gainesville, FL 32611 (US). (72) Inventors: GRAVENSTEIN, Dietrich; 3421 S.W. 79th Terrace, Gainesville, FL 32608 (US). LAMPOTANG, Samsun; 3916 S.W. 98th Drive, Gainesville, FL 32608 (US). MELKER, Richard; 6101 N.W. 19th Place, Gainesville, FL 32605 (US). GABRIELLI, Andrea; 1625 N.W. 61st Terrace, Gainesville, FL 32605 (US). (74) Agents: PARKER, James, S. et al.; Saliwanchik, Lloyd & Saliwanchik, Suite A-1, 2421 N.W. 41st Street, Gainesville, FL 32606-6669 (US).		(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GD, GE, HR, HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: MALLEABLE ENDOTRACHEAL TUBE WITH FIBEROPTIC SCOPE 		
(57) Abstract A system for imaging the human airway during the intubation procedure incorporates a malleable stylet which retains its shape when bent, in order to facilitate intubation of a patient. In a preferred embodiment, a solid metal stylet, for example, a conventional endotracheal stylet, can be utilized. The intubation scope allows for a user to utilize conventional techniques for the insertion of an endotracheal tube, reducing the training needed for use of the subject intubation scope. The imaging scopes also incorporate at least one illumination fiber to convey light to the distal tip of the subject imaging scopes, for illumination of the objects to be imaged.		

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DESCRIPTION

MALLEABLE ENDOTRACHEAL TUBE WITH FIBEROPTIC SCOPE

Background of the Invention

This invention relates to fiber optic imaging scopes and, in a particular embodiment, to intubation scopes. The subject intubation scopes can incorporate a malleable stylet, which can retain its shape when bent, to facilitate intubation. Advantageously, this invention can utilize plastic optical fibers to enhance the safety and efficacy of procedures performed with these novel fiber optic scopes, while simultaneously reducing the costs. Additionally, the scopes of the subject invention can, optionally, utilize a sheath which can reduce the amount of cleaning, *i.e.*, sterilization, required between uses and thereby reduce the costs of use.

It is frequently necessary in medical procedures to insert an endotracheal tube into the trachea of a patient for the purpose of performing diagnostic tests or for the introduction of some means of ventilation, oxygenation, and/or airway protection. Even in the best situations, intubation is often difficult and can give rise to complications. In many patients, establishment of the airway is particularly difficult due to morphologic anomalies such as a large tongue, excessive pharyngeal or laryngeal soft tissue, or tracheal displacement, as well as physiologic events such as laryngospasm, regurgitation of gastric materials, bleeding, or foreign bodies aspiration. These morphologic anomalies and/or events make it difficult to visualize the posterior pharyngeal area and larynx with conventional laryngoscopic maneuvers. In emergency situations, attempts to intubate such patients are difficult and time consuming. Inability to expeditiously intubate the patient and protect the airway can lead to significant hypoxemia, myocardial ischemia, and brain injury. Cases of death have also been related to complications caused by the inability to quickly and clearly see the larynx and trachea.

Proper intubation requires positioning the tip of the tracheal tube within the trachea, midway between the patient's vocal cords and carina. Direct laryngoscopy in many instances is sufficient to intubate the patient, but does not permit the precise confirmation of tip location or tracheal inspection.

If the tracheal tube is not inserted far enough past the vocal cords, the tube may become dislodged and prove to be ineffective in supporting adequate artificial ventilation. Further, the tube may inadvertently end up in the esophagus. Esophageal intubations, resulting from either dislodgement or incorrect initial placement have led to severe morbidity and even death. At the other extreme, if inserted too far and beyond the carina, the tube may only permit ventilation of

one lung (as opposed to both lungs). Thus, correct tube placement is essential in order to properly ventilate the patient.

Even the most skilled anesthesiologist may encounter what is commonly referred to as a "difficult" airway. This occurs in about 5% of all operating room intubations, with an even higher incidence of an inability to fully visualize the glottic opening. The incidence level is significantly higher in other areas of the hospital and prehospital environment. Although presurgical examination of the jaw, teeth, mouth opening and neck motion assists in gauging the degree of difficulty likely to be encountered at intubation, not all difficult intubations can be identified in advance. There is always the unexpected difficult airway, discovered only at the time of intubation. In emergency situations, there is little if any time to perform an airway assessment prior to attempting intubation. Thus, all emergency intubations are considered "difficult" intubations.

There are a number of techniques used to assist in difficult intubations. These include laryngoscopy, with or without axial cervical stabilization, fiberoptic bronchoscopy, with or without a transtracheal retrograde wire guide, blind nasal and the lighted stylet techniques.

Fiberoptic bronchoscopy is considered by many as the "gold standard" for viewing the airway and properly positioning a tracheal tube. The complexity of operating and cost of buying, maintaining, cleaning, and repairing existing glass fiberoptic systems, which are fragile, are major factors preventing greater usage of bronchoscopy.

The retrograde wire technique involves placing a needle into the cricothyroid space and advancing a guide wire through the needle and upward through the glottic opening between the vocal cords and pharynx until it emerges from the nose or mouth. After the wire is localized, a fiberoptic bronchoscope or tracheal tube is advanced over the wire into the larynx. This technique is not recommended in emergency situations. Major negative concerns associated with this technique are its invasive nature and the risk for bleeding and infection in the trachea. The wire can also cause injury to the tracheal tissue and/or vocal cords.

A lighted stylet is essentially a standard stylet with a bright light at the distal end. This technique provides only indirect transcutaneous illumination of the trachea. Direct visualization is not possible when using a lighted stylet.

Fiberoptic intubating scopes with cameras and/or eyepieces for viewing that which is illuminated by the fiber optic system have previously been described. See, for example, U.S. Patent Nos. 3,776,222; 4,742,819; 4,846,153 and 5,363,838. Current fiber optic scopes, for example, intubation scopes and associated systems for imaging the human airways, typically use glass optical fibers. Unfortunately, these intubation scopes and associated systems utilizing

glass optical fibers are expensive to purchase, clean, and store. Additionally, the glass optical fibers within these scopes are prone to breaking thereby shortening the life of the scopes.

Brief Summary of the Invention

5 The subject invention pertains to a system for imaging the human airway having highly advantageous optical, mechanical, ergonomical and physical characteristics. The subject system allows for a user to utilize conventional techniques for the insertion of an endotracheal tube while using the subject imaging scope. The excellent characteristics of the imaging system of the subject invention result, in part, from the use of plastic optical fibers. Plastic optical fibers
10 are more robust than the glass optical fibers used in currently available imaging systems, and are therefore capable of being bent and/or twisted with virtually no concern of breakage. In addition, the lower costs of plastic optical fibers enables scopes of the subject invention, in a specific embodiment, to be manufactured for single patient use thereby eliminating the requirement for cleaning, special care, the maintenance of expensive inventory, and most
15 importantly eliminating the opportunity for cross contamination between patients. A further aspect of the subject invention concerns a novel sheath which can cover all or a portion of the parts of the imaging system which enter the patient. This sheath can reduce the need for expensive sterilization of the subject intubation scope after use.

 An embodiment of the subject imaging system utilizing plastic optical fiber is highly
20 advantageous because of its longer life, increased ruggedness, greater flexibility, comparable image quality, optional disposability, and lower cost, compared to glass scopes. These scopes are useful, for example, for observing the bronchi of the lungs, locating the tracheal opening to allow insertion of an endotracheal tube into the trachea for intubation, and visually locating the endotracheal tube tip. Specifically, using a scope of the subject invention, a practitioner can
25 easily and precisely identify the exact location of the distal end of the tracheal tube, as well as the various anatomical airway landmarks. Currently, this degree of precision is only possible with an expensive glass fiberoptic bronchoscope. In addition, the scopes of this invention are particularly advantageous for use in anesthesiology.

 In a specific embodiment, the subject imaging system can incorporate a malleable stylet
30 which can retain its shape when bent. This embodiment can be used as an intubation scope. During an intubation, an anesthesiologist can insert the subject intubation scope into an endotracheal tube to be inserted into a patient. Once the intubation scope is inserted into the endotracheal tube, the anesthesiologist can bend the intubation scope - endotracheal tube combination into a shape, essentially any shape, which facilitates insertion into the patient.

Advantageously, the anesthesiologist can then hold the scope-tube combination in one hand, with a conventional grip, for example in a pen-like fashion, and easily maneuver the scope-tube combination during insertion into the patient.

While prior art scopes have required the anesthesiologist to change the standard procedure for inserting an endotracheal tube, for example by holding on to the scope and/or manipulating a handle on the scope to direct the tip of the scope, an anesthesiologist using the subject scope can hold the endotracheal tube in the conventional manner during intubation. This is an important improvement over the prior art because anaesthesiologists are not necessarily trained in endoscopy and without such additional training, would not normally be adept with the techniques for use of such prior scopes. The subject technology can therefore be referred to as a transparent technology, due to the minimal instruction needed before use thereof. Specifically, the subject invention allows an anaesthesiologist to hold the scope-tube combination with one hand during intubation and, for example, use a laryngoscope with the other hand, if necessary. In addition, the subject intubation scopes can be removed from the endotracheal tube, after insertion, with only one hand, thus freeing the anaesthesiologist's other hand. This is in contrast to many prior art scopes which require two hands for use, for example due to a twist motion needed to unlock the scope from the endotracheal tube.

In a specific embodiment, the subject invention pertains to a plastic optical fiber imaging scope, having an optional sheath, for intubation. This intubation scope can be used for intubation of patients under general and/or local anesthesia. The intubation scope of this embodiment can be disposable, sterilizable for reuse, or enclosed within a disposable sheath for reuse without expensive sterilization. Due to lower cost for the plastic optical fiber scopes, the scopes of the subject invention are particularly advantageous for situations calling for disposable scopes, and can be less expensive than the cleaning and sterilization costs for existing glass scopes.

Imaging scopes with varying components and corresponding performance capabilities can be manufactured with this new technology. By way of these multiple embodiments, the subject invention can be used for imaging essentially all of the airway system of humans and animals.

Brief Description of the Drawings

Figure 1 shows an embodiment of the intubation scope of the subject invention.

Figures 2A and 2D illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a plastic optical fiber image guide.

Figures 2B and 2E illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a plastic optical fiber image guide, wherein the sheath comprises an illumination fiber.

Figures 2C and 2F illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a stylet incorporated with a plastic optical fiber image guide, wherein the sheath comprises an illumination fiber.

Figure 3 illustrates markings and a hollow channel for ventilation, suction, and/or irrigation, in accordance with the subject invention.

Figures 4A and 4D illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of an embodiment of the subject invention comprising a stylet, an image guide, at least one illumination fiber, and rings to hold the components together.

Figures 4B and 4E illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of an embodiment of the subject invention comprising a stylet, an image guide, at least one illumination fiber, and an outer covering to hold the components together.

Figures 4C and 4F illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a flexible embodiment of the subject invention comprising an image guide, at least one illumination fiber, and an outer covering to hold the components together.

Figure 5 illustrates a specific embodiment of the subject invention comprising an image guide, at least one illumination fiber, and a stylet made of multiple wire strands.

Figure 6 illustrates an embodiment of the subject invention wherein an image guide, an illumination fiber(s), and a hollow channel are housed within a malleable stylet.

Figure 7 illustrates a preferred embodiment of the subject invention incorporating an image guide, an illumination fiber(s), and a malleable stylet, held together by an outer covering.

Detailed Disclosure of the Invention

The subject invention utilizes optical fiber to produce fiber optic scopes, and in a particular embodiment, intubation scopes, for use in imaging the human airway. In a preferred embodiment, the subject invention utilizes plastic optical fiber. The device of the subject invention can assist practitioners in properly introducing and confirming the position of tracheal tubes. Although the device has application in "difficult" intubations, use in all intubations is envisioned for confirming optimal tracheal tube advancement between the vocal cords and positioning within the trachea. This can only be achieved with direct tracheal visualization. The

plastic fiberoptic device of the subject invention makes this possible while also being highly cost effective.

The device of the subject invention has application for intubating patients undergoing general, intravenous and local anesthesia and in emergency situations. Thus, the device can be used in surgical procedures as well as in intensive care units, emergency departments and the prehospital settings.

The device of the subject invention can incorporate plastic fiberoptic technologies, enabling direct visualization of the pharynx, glottic opening, larynx and trachea and thus, facilitate accurate tracheal tube placement and periodic verification of tracheal tube tip location. Further, the subject device can easily be steered, simplifying proper tube placement. Traditional reusable glass fiber bronchoscopes are expensive to purchase and maintain. Effectively cleaning the bronchoscope is difficult. It is also recognized that sterility of existing reusable glass fiber bronchoscopes is often not achieved after use with a patient.

The subject invention achieves substantial improvements in performance compared to existing glass fiber scopes, including: (1) longer life; (2) increased ruggedness; (3) greater flexibility; (4) optional disposability; (5) greater ease of use; and (6) less expense. By varying the components of the intubation scopes utilizing the teachings of the subject invention, these performance characteristics can be optimized, to facilitate the use of these scopes for imaging a vast portion of the human airways and in a variety of situations. Thus, the scopes of the subject invention can be used, for example, for observing the bronchi of the lungs, locating the tracheal opening to allow insertion of an endotracheal tube into the trachea for intubation, and locating the endotracheal tube tip. In particular, an anesthesiologist can, using the scope of the subject invention, stand behind the head of a patient while performing an intubation. Additionally, this device will reduce the force necessary for laryngoscopy. Reduced force leads to less tissue trauma, hemodynamic changes, and post-operative sore throat complications. Advantageously, the scopes of the subject invention are more cost effective in situations requiring a disposable scope and/or can be used with an optional disposable sheath to enclose the portion of the scope entering the body to reduce cleaning and sterilization costs.

In one embodiment the light source can be derived from a standard laryngoscope. In a second embodiment, one or more optical fiber(s) can transmit the light required to illuminate the airway. The source of the light can be, for example, a laryngoscope or an inexpensive separate light source.

Image guides used in conjunction with intubation, for example, bronchoscopes, are typically made with step index glass optical fiber. Plastic optical fiber can also be fabricated

with a step index of refraction. Both plastic and glass step index fibers are constructed with a core of refractive index n_1 , and a cladding of refractive index n_2 , where $n_1 > n_2$. A second type of fiber is known as gradient index or graded index fiber and can also be made with plastic or glass. Since flexibility is an important characteristic for the scopes of the subject invention, plastic gradient index optical fibers are preferred over glass gradient index optical fibers for the subject image guides.

In comparing the step index structure with the gradient index structure, it is noted that there are different trajectories of light rays in these two fiber structures. Within step index fiber, the light travels in straight lines, and is reflected at the core-cladding interface. While in gradient index fiber, the light travels in a curved trajectory always being refracted back towards the axis of the fiber. As a consequence, an image can be conveyed within a single gradient index fiber, while an image cannot be conveyed within a single step index fiber. Although, when conveying an image in a single gradient index fiber, some correction may be required to correct aberrations in the output image, for example, by using one or more negative gradient index lens attached to one or both ends of the single gradient index fiber.

Referring to Figure 1, the intubation scope of the subject invention comprises an image guide 1, which conveys optical images from inside the body, for example from inside the human airways, to outside of the body for viewing by a medical caregiver. In a specific embodiment, this image guide 1 can comprise a single gradient index plastic optical fiber. In a specific embodiment, this single fiber can have a diameter, for example, of about 0.5 to 2.0 mm. A focusing lens 2 can optionally be used to focus the desired image into the distal tip 7 of the single fiber, the distal tip 7 entering the body, generally through the mouth or nose. This lens 2 can be attached by, for example, optical glue, and can act as a bi-convex lens to focus the desired image onto the distal tip of the single fiber. In this single fiber embodiment, a negative gradient rod lens, made of glass or plastic, can be attached to the proximal end of the single fiber image guide 1 and used to correct for aberrations resulting from the use of a single gradient index plastic optical fiber to carry the image.

In an alternative embodiment, this image guide 1 can comprise a bundle of plastic optical fibers. This plastic fiber optic image guide 1 can be made of a plurality of individual plastic optical fibers which have been fused together. In a specific embodiment, this bundle can comprise approximately 10,000 individual plastic optical fibers, wherein the bundle is approximately 1.0 millimeter in diameter. This bundle can comprise gradient index plastic optical fibers and, in a preferred embodiment, this bundle can comprise step-index plastic optical fibers. Each end of the bundle can be polished to allow high resolution imaging. A focusing

lens 2 can be used to focus the desired image onto the distal tip 7 of the bundle, the distal tip 7 entering the human body, generally through the mouth or nose. This lens 2 can be attached at the distal tip 7 of the bundle, for example, by optical glue 4. This lens 2 can act like a bi-convex lens to focus the image onto the distal tip of the fiber optic bundle. In a preferred embodiment, the lens 2 can be a gradient-index glass rod lens. In a more preferred embodiment, the lens 2 can be a gradient-index plastic rod lens.

An optical system can transmit the image from the proximal end of the fiberoptic image guide 1 onto a charge coupled device (CCD). The CCD can be used to convert the image into an electrical signal which can be displayed on a monitor. Alternatively, camera equipment available to the physician can be used. In a specific embodiment, the proximal tip 8 of the image guide 1 is arranged so that the image from inside the patient is focused directly onto an imaging eyepiece 6. The imaging eyepiece 6 can be connected to a camera for viewing the image, or the image can be viewed directly by the medical caregiver through the imaging eyepiece 6.

In an alternative embodiment, when a camera is not to be used for viewing the image, a second lens 3 can be attached, for example, by optical glue 5, to the proximal tip 8 of the image guide 1, the proximal tip remaining outside of the body. This lens can be, for example, a mini plastic lens microscope connected directly to the proximal end of the fiber scope for direct viewing by the caregiver, i.e., by placing an eye to the microscope lens. In a specific embodiment, the fiberoptic image guide can be lengthened and mini plastic lens microscope can be mounted on a caregiver's head, for example, by a mounting means such as a pair of glasses or goggles. This allows the caregiver to have both hands free to perform, for example, an intubation, while being able to view the patient and the image from the scope without having to turn his or her head.

Manufacturing the subject invention without a camera can be done to reduce costs or to meet the needs of certain medical situations. However, when the eyepiece is connected to a camera, the image can be displayed via, for example, a television monitor. This monitor can be, for example, placed out of the sterile field for viewing.

In a specific embodiment, the visualization system scope of the subject invention can be inserted into a plastic tube (sheath), which can have a transparent end plate. This combination can then be used for imaging the airway. The image viewed through the end plate is unimpaired by the sheath or end plate. The advantage of this sheath is that it is disposable and allows the intubation scope to be reused with minimal sterilization.

In a preferred embodiment, the sheath can have at least one internal, or external, illuminating optical fiber(s) which transmits light to illuminate the internal body structure to be

imaged. Additionally, it is preferred but not essential, that there be no transparent end-plate at the distal end of the illuminating optical fiber(s) to avoid the illuminating light reflecting at such a plate and impairing the quality of the image. A longitudinal cross section and a transverse cross section of a sheath comprising an external illumination fiber are shown in Figures 2B and 2E, respectively.

When performing, for example, an intubation, a malleable stylet, typically made of metal, is often used in conjunction with an endotracheal tube to facilitate the placement of the tube into the body. In a specific embodiment, the subject intubation scope can incorporate a stylet, wherein the stylet can be bent into the shape which the caregiver believes will facilitate the easiest and safest placement of the endotracheal tube, and then the endotracheal tube, which typically surrounds the stylet and scope, can be inserted into the patient. A longitudinal cross section and a transverse cross section of a sheath comprising an external illumination fiber, where the sheath is designed to fit over a stylet incorporated with a plastic optical fiber image guide, are shown in Figures 2C and 2F, respectively. In this case, the sheath and illuminating fiber could be regarded as disposable after a single use.

Accordingly, the intubation scope and/or sheath of the subject invention can comprise such a stylet, such that many combinations of scope, stylet, illuminating fiber(s), and sheath are possible. In accordance with the subject invention, the combination of an image guide and a malleable stylet, which retains its shape when bent, facilitates the placement of an endotracheal tube into a patient. In a preferred embodiment, a solid metal stylet, for example a conventional endotracheal tube stylet, can be utilized. The image guide can be attached to the stylet such that the image guide takes essentially the same shape as the stylet when the stylet is bent. In a specific embodiment, referring to Figure 6, the image guide can be incorporated into the stylet. Accordingly, the stylet-image guide combination, i.e., the intubation scope, can be inserted into an endotracheal tube which is to be inserted into a patient. In a more preferable embodiment, the intubation scope can also comprise an illumination fiber, for example also attached to the stylet. Once the intubation scope is inserted into the endotracheal tube, a caregiver can bend the endotracheal tube into the shape, essentially any shape, which the caregiver believes will facilitate the easiest and safest insertion of the endotracheal tube. In fact, a caregiver can insert the tube-scope combination into a patient using one hand to hold and maneuver the tube-scope combination. Once the tube-scope combination is in place in the patient, a caregiver can, again with one hand, remove the subject intubation scope from the endotracheal tube.

A variety of attachment means can be utilized in accordance with the subject invention to attach the stylet, image guide, and/or illuminating fiber. It is preferred that the relative

position of the distal tip of the image guide and the distal tip of the illumination fiber remain fixed, both in angular orientation and axial translation, in order to enhance the quality of the image. In addition, it is preferred that the relative position of the distal end of the stylet also remain fixed with respect to the distal tip of the image guide.

5 Referring to Figures 4A and 4D, a specific embodiment of the subject invention is shown where the distal ends of a stylet, an image guide, and an illumination fiber are securely attached to each other via an attachment means, for example with glue or a clip. This embodiment also includes rings, for example made of an appropriate elastic material, which hold the various components together along the length of the intubation scope. These rings can allow
10 for slippage of the various components, for example during the bending of the intubation scope, while maintaining the relative positions of the distal ends of the various components.

Alternatively, referring to Figures 4B and 4E, an outer covering can be used to hold the various components together. This outer covering can be made of a material, for example a polymer, which can alter, either increase or reduce, the friction between the subject intubation
15 scope and the inside of an endotracheal tube. For example, reduced friction can facilitate the removal of the subject intubation scope after intubation of a patient. Again, it is preferred that the relative positions of the distal ends of the various components remain constant. In an additional embodiment, a transparent end covering can be utilized to cover the distal tip of the intubation scope.

20 Figures 4C and 4F show an embodiment of the subject invention which can be referred to as a noodle. This embodiment does not incorporate a stylet and, therefore, can be useful, for example, for nasal intubations. This embodiment can also be used, for example, to check the position of the distal tip of an endotracheal tube which is in place in a patient.

Stylets of various cross-sectional shapes can be used in accordance with the subject
25 invention. A variety of materials for producing the stylet are also envisioned within the scope of the subject invention, for example polymers, metals, or other materials having the proper physical characteristics. It is important for the stylet to be malleable such that the stylet can be bent and will retain its shape when bent. Preferably, the subject stylet can be bent easily by a user into essentially any shape which will facilitate the insertion.

30 In addition, the subject intubation scopes can have a coating, for example a polymer coating. In a specific embodiment, this coating can be placed around a solid cylindrical rod made of a malleable metal. The coating can be used to modify friction between the endotracheal tube and the subject scope so as to optimize movement of the scope within the tube. For example, a low friction coating may decrease friction between the scope and the endotracheal

tube so as to ease withdrawal of the scope from the tube. Various cross-sectional shapes for the subject intubation scopes are also possible. For example, referring to Figure 5, the subject scope can incorporate a stylet comprising multiple, thinner rods which can be positioned circumferentially around the image guide. If illumination fibers are utilized, these illumination fibers can also be positioned circumferentially around the image guide, for example interspaced with the multiple rods of the stylet. In addition, a coating and/or an outer covering can be applied to the outside of the intubation scope to assist in holding the multiple stylets and multiple illumination fibers to the side of the image guide. This coating may allow for reuse of the subject scope, for example after cleaning.

In an additional embodiment, referring to Figure 6, an outer covering around the subject image guide can act as a stylet, for example if the outer coating is malleable and retains its shape when bent. The embodiment shown in Figure 6 comprises a malleable stylet having hollow channels where an image guide and illumination fiber(s) can reside. This stylet can, for example, be extruded such as to have these channels. As also shown in Figure 6, an additional channel can be provided for injection, ventilation, suction, and/or irrigation. In a preferred embodiment, the subject imaging scopes have no moving parts other than that resulting from bending of the stylet, image guide, any illumination fibers, and other lumens.

Preferably, during insertion of an endotracheal tube into a patient, the distal tip of the image guide can reside near the distal tip of the endotracheal tube such that a caregiver receives images from near the distal tip of the endotracheal tube, so as to facilitate proper placement of the tube. In addition, it is preferable that the distal tip of the stylet and image guide do not extend from the distal tip of the tube where they may injure the trachea or other areas during the insertion of the tube. To prevent the distal tips of the stylet and image guide from traveling past the distal tip of the tube, the stylet can be bent near the proximal end of the tube, for example bent over the proximal end of the tube. The image guide can be bent as well, for example if attached to the stylet of the scope at the proximal end of the tube, or can move independently from the stylet.

In a preferred embodiment of an intubation scope in accordance with the subject invention, as illustrated in Figure 7, the proximal end of the stylet can terminate, for example in a loop, at a length slightly longer than an endotracheal tube into which it is to be inserted. Such a loop can allow a caregiver to easily grasp the stylet end to bend the stylet end over the proximal end of the tube. In addition, a looped proximal end of the stylet can assist in removal of the scope from the tube. For example, a user can hold the end of the tube with one hand and use the thumb on the same hand to move the scope out of the tube by hooking the loop with the

thumb. Advantageously, due to the lightweight image guide and illumination fiber(s), the center of gravity of the endotracheal tube - intubation scope combination can be located in essentially the same location along the endotracheal tube as with a conventional stylet inserted in an endotracheal tube, such as to provide good balance in the user's hand during intubation. This allows the center of balance of the tube-scope combination in a user's hand to remain in essentially the same position as for a conventional endotracheal tube-stylet combination.

In accordance with the subject invention, the ability of a caregiver to hold the endotracheal tube itself during insertion into a patient has many advantages. By holding the tube with a conventional, or pen-like, grip a caregiver can twist or rotate the tube, as well as move it translationally, with more leverage than if held by, for example, a scope inserted into the tube. During the insertion, a caregiver can view the image from the image guide on, for example, a monitor, without the need to view the patient directly.

In addition, the ability to bend the scope-tube combination in essentially any shape prior to insertion of the tube into a patient can reduce the risk of injury to a patient whose anatomy may require a tailored bend. Advantageously, insertion of the tube can then be performed on a patient in the neutral position. Prior art devices have required the patient to be in a "sniffing" position or to have the head tilted back to create a straighter insertion channel, due in part to the stiffness and limited range of motion of the prior devices. Insertion of the tube while a patient is in the neutral position, as opposed to the sniffing or head-tilted-back positions, results in reduced increases in blood pressure, heart rate, and reduced injury to the trachea. In addition, the ability to bend the scope-tube combination in essentially any shape allows the tube to be preformed to a shape tailored specifically to a patient, prior to insertion of the tube. This allows insertion of the scope-tube combination while a patient is in the neutral position, and can thus eliminate the need for a laryngoscope to elevate tissues. If preferred, a laryngoscope can be used to move the tongue out of the way such that the tube-scope combination can be inserted. However, there is no need to use the laryngoscope to further elevate tissues, for example to see the larynx. The subject tube-scope is preferably rigid enough so that a laryngoscope is not necessary. The scope can sweep the tongue away, eliminating the need for a laryngoscope, thus reducing complications, such as chipped teeth. In addition, less force can be applied, reducing injuries. This allows intubation to be performed while a patient is awake or asleep, in an elective or emergency situation. In addition, the ability to intubate a patient in the neutral position can prevent further injury to a patient with, for example, known or possible neck or spine injuries. Patients with known or possible cervical spine instability or fused/fixed spine can be intubated and/or examined without having to be moved.

In a specific embodiment in accordance with the subject invention, an intubation scope can have a removable stylet. The stylet can be removed to perform, for example, nasal intubation or stoma/tracheotomy. In addition, this embodiment can allow for insertion of an endotracheal tube, utilizing the intubation scope with the stylet attached, and the subsequent
5 verification of the tube's position, utilizing the intubation scope with the stylet removed. In another embodiment, the subject scope can have no stylet. This embodiment can be useful for confirmation of the endotracheal tube location and inspection of patients' tissues and structures, for example to reduce the need for x-rays. Figures 4C and 4F illustrate one such embodiment.

In a specific embodiment of the subject intubation scope, a charge-coupled device
10 (CCD) can be mounted at the distal tip of the stylet, which can eliminate the necessity for an optical fiber image guide. The signal generated from the CCD can be carried, for example via wires, to a camera external to the endotracheal tube. This camera can be located in any position which allows a caregiver to conveniently view the camera during intubation of the patient. In a further embodiment, the CCD and camera can be located at the proximal end of the stylet, such
15 that an image is carried from the distal tip of the endotracheal tube to the CCD by an image guide during intubation.

Once the subject intubation scope is inserted into an endotracheal tube and secured in place, for example by bending the proximal end of the stylet over the proximal end of the endotracheal tube, the image carried from the distal tip of the image guide to the proximal end
20 of the image guide needs to be viewed by the caregiver. In a preferred embodiment, the proximal end of the image guide can terminate with a quick-connect connector such that the proximal end of the image guide can easily plug into a device for receiving and displaying the image. Quick-connect connectors are particularly advantageous when a plastic optical fiber image guide and plastic optical fiber illumination fibers are utilized, due to greater misalignment
25 tolerances than with glass optical fiber. The proximal end of any illumination fibers can also terminate with quick-connect connectors such that easy connection to an illuminating light source is possible. In a specific embodiment, slide and lock quick-connect connectors may be utilized. The use of quick-connect connectors allows for a free flexible tail and a lightweight intubation scope. The use of slide and lock quick-connect connectors can assist a caregiver in
30 maintaining proper orientation of the image being viewed and prevent the connector from coming loose during operation, thus enhancing performance.

A preferred embodiment of an intubation scope in accordance with the subject invention is illustrated in Figure 7. The proximal ends of the illumination fiber and image guide can form a free flexible tail which is lightweight. Accordingly, after insertion of the subject intubation

scope into an endotracheal tube, the scope-tube combination can be maneuvered easily and has the same feel in a user's hand as the conventional tube with a conventional stylet inserted. The quick-connect connectors can be connected just before placement of the scope-tube combination into the patient, allowing the caregiver considerable freedom of maneuverability while inserting the intubation scope into the endotracheal tube.

The intubation scope and method of tracheal tube placement verification of the subject invention represents a significant cost saving for the hospital. Rather than having to periodically x-ray the patient to verify tube position, the hospital staff can use the subject invention to not only confirm proper tube placement but to also evaluate the airway for obstruction and/or erosion, which is not possible with x-rays. Advantageously, the use of the subject technology can reduce a patients exposure to x-rays.

The device of the subject invention is easily connected to bronchoscope imaging equipment, without incurring the cost of buying and sterilization processing of the bronchoscope. In another embodiment, an off the shelf LCD device similar to a Sony "WATCHMAN" can be utilized for imaging.

Following are examples which illustrate procedures for practicing the invention. These examples should not be construed as limiting.

Example 1

The device of the subject invention not only makes intubation easier and more accurate, but also reduces the potential for inflicting injury with the laryngoscope blade. Using the device of the subject invention, the practitioner only needs to use the laryngoscope blade to control the position of the patient's tongue. The device can also be used without a laryngoscope and for nasotracheal intubation.

The device of the subject invention can comprise a bundle of 10,000 individual plastic optical fibers (bundle is approximately 1.0 millimeter in diameter). The resolution of the image is comparable to an existing glass fiberoptic bronchoscope, providing good visualization of the patient's airway.

The manufacturing process places the bundle integral to a standard malleable stylet. An additional fiber may be used for illuminating purposes. Suctioning and insufflation can be added by adding an additional channel if desired.

A focusing lens (*i.e.*, gradient refractive index lens) is placed at the distal tip of the optical fibers and acts like a bi-convex lens to focus the image onto the distal tip of the fiber

optic bundle. An optical system transmits the image from the proximal end of the fiberoptic bundle onto a charge coupled device (CCD). The CCD is used to convert the image into an electrical signal which can be displayed on a monitor. Alternatively, camera equipment available to the physician may be used.

Example 2

Referring to Figures 2A, 2B, 2C, 2D, 2E, and 2F, this example provides three illustrative combinations of image guide, illuminating fiber, stylet, and/or sheath. Figures 2A and 2D illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a plastic optical fiber image guide. The sheath covers the distal tip of the image guide with a transparent end plate. In this case, any illuminating fibers and/or stylets would not be enclosed within this sheath, although they could have their own sheaths.

Figure 2B and 2E illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a plastic optical fiber image guide, wherein the sheath comprises an illumination fiber. The distal end of the illumination fiber is not covered by the sheath, in this example, so as to not impair the image. Accordingly, the illuminating fiber can be disposed of with the sheath. In this embodiment, the sheath acts to attach and position the illumination fiber with respect to the image guide.

Figures 2C and 2F illustrate a longitudinal cross section and a transverse cross section, respectively, of the distal end of a sheath designed to fit over a stylet incorporated with a plastic optical fiber image guide, wherein the sheath comprises an illumination fiber. The distal end of the illumination fiber is not covered by the sheath, but the distal end of the image guide plus stylet is covered. In this embodiment, the stylet can be reused along with the image guide. Other geometrical arrangements of the stylet, image guide, and illumination fiber are obviously possible.

Example 3

It is sometimes necessary to replace an endotracheal tube in a patient, for example when the tube no longer provides an adequate airway. In a specific embodiment, the subject invention can permit the easy removal of one endotracheal tube and its replacement with a new one.

A device in accordance with the subject invention can be inserted into the patient's trachea, generally through an existing tracheal tube, until the distal tip is at or near the tip of the tube. Oxygen for ventilation, suction or irrigation can also be applied in succession via, for

example, quick fit connectors to the proximal end if desired. Once the anatomy is visualized, the light source, camera or eyepiece, and oxygen/suction/irrigation can all be disconnected from the proximal end of the subject device. The endotracheal tube can then be completely removed by sliding it out of the trachea, along, and off the proximal end of the subject device. The connectors of the subject device can be of a suitable diameter and located at different positions relative to the proximal end to permit their passage through the tracheal tube. The new tracheal tube can be loaded onto the subject device and the illumination and visualization equipment reconnected. The tracheal tube can be advanced down into the trachea while observing the airway anatomy via the subject device. Preferably, the subject device can be rigid enough to maintain its location in the trachea as it guides a replacement endotracheal tube into the trachea.

Alternatively, the image guide and illumination fiber(s) can remain connected until the endotracheal tube to be replaced has been slid out of the trachea. This allows continuous monitoring of the location of the distal tip of the tube exchanger, reducing the risk of the tube exchanger being dislodged during removal of the endotracheal tube. Once the tube is completely out of the patient, the proximal ends of the image guide and illumination fiber(s) can be disconnected to slide the tube off of the exchanger and slide a new tube onto the exchanger. The image guide and illumination fiber can then be reconnected to confirm the position of the exchanger before and during the placement of the new tube into the patient.

In order to utilize the subject invention during the exchange of an endotracheal tube, the fiber optic bundle can, preferably, be approximately the same length as a commercially available endotracheal tube exchanger, for example about 80-100 cm. In addition, referring to Figure 3, markings can be provided on its wall indicating, for example in 5 cm increments, the length from its distal end to any given mark. This can allow the clinician to better gauge whether the distal tip is likely to be in the oropharynx, trachea, bronchus or beyond and can therefore improve patient safety.

Example 4

Referring to Figure 3, the subject invention, for example the devices disclosed in the previous examples, can have a hollow channel of sufficient caliber to provide adequate jet ventilation, suction and/or irrigation, if desired. Accordingly, if mucus plugs are visualized they can be suctioned and if secretions obstruct vision, the lens can be cleaned with irrigation through the hollow channel. Advantageously, ventilation can be provided through the hollow channel during the exchanging of endotracheal tubes.

5 The subject invention can also incorporate deflection, for example of about 0-60°, between about 1-10 cm from the distal tip, to allow a clinician to direct the subject device down either bronchus, towards a mucus plug, or away from the tracheal wall, simply by rotating the device along its length. This deflection may be incorporated into a device such that the distal tip of the subject scope conforms to the shape of an endotracheal tube while within the tube. When the distal end of the scope is advanced past the distal end of tube, the tip can assume a predefined deflection, for example due to memory in the stylet.

10 It should be understood that the examples and embodiments described herein are for illustrative purposes only and that various modifications or changes in light thereof will be suggested to persons skilled in the art and are to be included within the spirit and purview of this application and the scope of the appended claims.

Claims

1 1. A scope, comprising an image guide and a malleable stylet which retains its shape
2 when bent.

1 2. The scope, according to claim 1, wherein said image guide is attached to said stylet
2 such that the image guide takes essentially the same shape as the stylet when the stylet is bent.

1 3. The scope, according to claim 1, wherein said scope can be inserted into an
2 endotracheal tube creating a tube and scope combination, and wherein the tube and scope
3 combination can be bent into a shape, which facilitates placement into a patient, such that the
4 tube and scope combination retains such shape due to the stiffness of the stylet.

1 4. The scope, according to claim 3, wherein said tube and scope combination can be
2 bent into a shape which facilitates placement of an endotracheal tube into a patient in the neutral
3 position.

1 5. The scope, according to claim 3, further comprising a means for limiting the
2 movement of said scope within said endotracheal tube after insertion of said scope into said
3 endotracheal tube.

1 6. The scope, according to claim 3, wherein after insertion of the scope into the
2 endotracheal tube, the proximal end of said stylet can be bent over the proximal end of said
3 endotracheal tube such as to limit the movement of the scope within the endotracheal tube.

1 7. The scope, according to claim 6, wherein after the proximal end of said stylet is bent
2 over the proximal end of said endotracheal tube, the scope can still be removed.

1 8. The scope, according to claim 3, wherein said scope, upon insertion into said
2 endotracheal tube, can be bent over the proximal end of said endotracheal tube such as to limit
3 the movement of the scope within the endotracheal tube.

1 9. The scope, according to claim 8, wherein after said scope is bent over the proximal
2 end of said endotracheal tube, the scope can still be removed.

1 10. The scope, according to claim 6, wherein once (i) the scope is inserted into the
2 endotracheal tube; (ii) the proximal end of the stylet is bent over the proximal end of the
3 endotracheal tube; and (iii) the tube and scope combination is bent into a shape which facilitates
4 placement into said patient, a caregiver can hold the tube and scope combination by the tube for
5 placement into a patient.

1 11. The scope, according to claim 8, wherein once (i) the scope is inserted into the
2 endotracheal tube; (ii) the scope is bent over the proximal end of the endotracheal tube; and (iii)
3 the tube and scope combination is bent into a shape which facilitates placement into a patient,
4 a caregiver can hold the tube and scope combination by the tube for placement into said patient.

1 12. The scope, according to claim 3, wherein, upon insertion of said scope into an
2 endotracheal tube creating a tube and scope combination, said tube and scope combination can
3 be held by a caregiver with one hand during placement of said tube and scope combination into
4 said patient.

1 13. The scope, according to claim 12, wherein said caregiver can hold said tube and
2 scope combination in a conventional pen-like grip during placement of said tube and scope
3 combination into said patient.

1 14. The scope, according to claim 3, wherein, after insertion of the scope into the
2 endotracheal tube, friction between the endotracheal tube and scope allows the tube and scope
3 combination to be turned and translated in essentially any direction during placement into a
4 patient while maintaining the relative position of the intubation scope to the endotracheal tube.

1 15. The scope, according to claim 1, wherein said image guide and said stylet are non-
2 coaxial.

1 16. The scope, according to claim 1, wherein said malleable stylet comprises a solid
2 rod.

1 17. The scope, according to claim 1, wherein said malleable stylet comprises a lumen
2 capable of holding an image guide.

1 18. The scope, according to claim 1, wherein said malleable stylet comprises a plurality
2 of solid rods.

1 19. The scope, according to claim 1, wherein said image guide is held in essentially a
2 constant relative position to said stylet by an outer covering.

1 20. The scope, according to claim 1, wherein said stylet is removable such that the
2 scope, without the stylet attached, can be inserted into an endotracheal tube which is already
3 positioned in a patient, without the scope altering the position or shape of said endotracheal tube.

1 21. The scope, according to claim 1, wherein said stylet can be bent in essentially any
2 direction at any location along the length of said stylet.

1 22. The scope, according to claim 1, further comprising an illumination fiber for
2 transmitting light to the distal end of said scope.

1 23. The scope, according to claim 1, wherein the image guide is attached to the stylet
2 near the distal end of the scope.

1 24. The scope, according to claim 1, wherein said scope is an intubation scope, and
2 wherein the image guide is attached to the stylet beginning near the distal end of the scope for
3 a length of attachment of approximately the length of an endotracheal tube into which the
4 intubation scope is to be inserted.

1 25. The scope, according to claim 1, wherein said scope is an intubation scope, and
2 wherein the image guide is attached to the stylet beginning near the distal end of the scope for
3 a length of attachment less than the length of an endotracheal tube into which the scope is to be
4 inserted.

1 26. The scope, according to claim 1, wherein the image guide is attached to the stylet
2 near the distal end of the scope, further comprising at least one ring(s), wherein said ring(s) hold
3 the image guide and stylet together along the length of the scope.

1 27. The scope, according to claim 24, wherein the stylet terminates at a distance of
2 about one inch to about three inches from the point of separation of the image guide and stylet.

1 28. The scope, according to claim 1, wherein the proximal end of said image guide
2 comprises a quick-connect optical connector.

1 29. The scope, according to claim 28, further comprising at least one illumination fiber,
2 wherein the proximal end of said illumination fiber comprises a quick-connect optical connector.

1 30. The scope, according to claim 28, wherein said quick-connect optical connector is
2 a slide and lock type quick optical connector.

1 31. The scope, according to claim 1, further comprising means for performing one of
2 the following: ventilation, suction, injection, and irrigation.

1 32. The scope, according to claim 1, further comprising a port which can allow for one
2 of the following: ventilation, suction, injection, and irrigation.

1 33. The scope, according to claim 3, wherein said tube and scope combination is
2 sufficiently stiff to allow a caregiver to sweep a patient's tongue out of the way with the tube and
3 scope combination during the placement of the tube and scope combination into said patient.

1 34. The scope, according to claim 3, wherein a center of gravity of said tube and scope
2 combination lies within said endotracheal tube.

1 35. A scope kit comprising an image guide and a malleable stylet which retains its
2 shape when bent.

1 36. A scope comprising an image guide and an illumination fiber, wherein said scope
2 is sufficiently flexible so as to be used for nasal intubation.

1 37. The scope, according to claim 1, wherein said scope incorporates a deflection at the
2 distal tip of said scope such that the distal tip of said scope conforms to the shape of an

3 endotracheal tube while within the tube, and assumes a predefined deflection when the distal tip
4 of said scope is advanced past the distal end of the endotracheal tube.

1 38. A scope, comprising an image guide for conveying optical images and a means for
2 retaining the shape of the scope when bent.

1 39. A method of exchanging endotracheal tubes, said method comprising the steps of:
2 (a) inserting an intubation scope, said intubation scope comprising an image guide, into
3 an endotracheal tube to be replaced, wherein a proximal end of said intubation scope is
4 connected to a viewing system to allow a user to view images of a patients airway;

5 (b) completely withdrawing the preexisting endotracheal tube from the patient;

6 (c) disconnecting the proximal end of said intubation scope from said viewing system;

7 (d) withdrawing the preexisting endotracheal tube over the proximal end of said
8 intubation scope;

9 (e) loading a new endotracheal tube onto the proximal end of said intubation scope;

10 (f) reconnecting the proximal end of said intubation scope to the viewing system; and

11 (g) advancing the new endotracheal tube into its proper position while observing the
12 anatomy of the airway through said image guide.

1 40. The method, according to claim 39, wherein said intubation scope further comprises
2 a hollow channel which allows one or more of the following: ventilation, suction, injection, and
3 irrigation.

1 41. The method, according to claim 39, wherein said intubation scope further comprises
2 markings which indicate the distance from the distal end of said intubation scope to assist in
3 estimating the location of the distal end of said intubation scope.

1 42. The method, according to claim 39, wherein said intubation scope further comprises
2 a deflection at the distal end of said intubation scope to assist a user in the placement of said
3 intubation scope.

1 43. A scope, comprising an image guide and a body, wherein said scope is used for
2 exchanging an endotracheal tube of a patient, wherein said body is rigid enough to maintain its
3 location in the trachea as said scope guides a replacement endotracheal tube into the trachea.

1 44. The scope, according to claim 43, further comprising a connector located at a
2 proximal end of said image guide to connect to a viewing system, wherein said connector is
3 small enough such that an endotracheal tube can pass over said connector.

1 45. The scope, according to claim 44, further comprising at least one illumination
2 fiber(s) and a connector located at a proximal end of said illumination fiber(s), wherein said
3 connector can connect to a light source, and wherein said connector is small enough such that
4 an endotracheal tube can pass over said connector.

1 46. The scope, according to claim 45, wherein the image guide connector and the
2 illumination fiber(s) connector are staggered so as to facilitate removal of said endotracheal
3 tube.


1 47. The scope, according to claim 1, wherein said stylet and said image guide are
2 attached such that the relative position of the distal tip of said stylet and the distal tip of said
3 image guide are maintained.

1 48. The scope, according to claim 24, wherein said stylet and said image guide are
2 attached via an outer covering or coating.
3

4 49. The scope, according to claim 39, further comprising a transparent end covering at
5 the distal end of said scope.

1 50. The scope, according to claim 22, wherein said scope can be utilized as a lighted
2 stylet.

1
G.
F






FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F

FIG. 3




FIG. 4D




FIG. 4A

FIG. 4E





FIG. 4B

FIG. 4F



FIG. 4C







FIG. 5






FIG.7

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/00740

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61B1/267

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 329 940 A (E.L. ADAIR) 19 July 1994---	1-5, 12-15, 17, 19-26, 28-32, 35, 38 43, 46, 47 39, 40
X A	see column 2, line 8 - column 3, line 25 see column 5, line 14 - column 8, line 63 ---	
X	US 4 742 819 A (G.P. GEORGE) 10 May 1988 cited in the application	1-5, 12-14, 16, 17, 19, 21-25, 27 36-38, 47 39, 42, 43
X A	see column 2, line 52 - column 3, line 9 see column 3, line 55 - column 4, line 47 ---	
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 March 1999

Date of mailing of the international search report

07/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Rieb, K.D.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/00740

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 363 838 A (G.P. GEORGE) 15 November 1994 cited in the application	1-5, 12-14, 17, 21-25,31
X	see column 3, line 55 - column 4, line 17	32,35-38
X	see column 4, line 47 - column 5, line 37	42,43,47
A	see column 6, line 17 - line 40 ---	39,40
P,X	WO 98 14112 A (UNIVERSITY OF FLORIDA) 9 April 1998	1-4,15
X	see page 8, line 5 - line 22	17,29-34
X	see page 9, line 3 - line 15	28,29,31
X	see page 9, line 30 - page 11, line 6 ---	32,35, 37-46,49
A	DE 41 32 687 A (T. KROMER) 8 April 1993	1-5
A	see column 3, line 4 - line 16	12-14,19
A	see column 3, line 32 - column 4, line 37 ---	21-26,47
A	US 3 417 746 A (W.C. MOORE ET AL.) 24 December 1968	1,5,14
A	see column 1, line 13 - line 21 see column 3, line 47 - line 68 see column 4, line 19 - line 29 -----	22,40,41

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Patent Application No

PCT/US 99/00740

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5329940 A	19-07-1994	CA 2035488 A	15-08-1991
		EP 0515487 A	02-12-1992
		JP 6504209 T	19-05-1994
		WO 9112044 A	22-08-1991
US 4742819 A	10-05-1988	NONE	
US 5363838 A	15-11-1994	NONE	
WO 9814112 A	09-04-1998	NONE	
DE 4132687 A	08-04-1993	NONE	
US 3417746 A	24-12-1968	NONE	

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning these documents will not correct the image
problems checked, please do not report these problems to
the IFW Image Problem Mailbox.**

This Page Blank (uspto)